

# INDUSTRIAL LIGHTING

## CPANL™ SWITCHABLE LUMEN FLAT PANEL LIGHT FIXTURE

- An edge-lit flat panel that provides a glare-free luminous appearance
- Provides superior ambient lighting perfect for commercial applications such as retail spaces, offices, hospitality and education
- Its low-profile design provides increased installation flexibility especially in restricted plenum spaces
- The switchable lumen feature allows you to toggle between 3 preset lumen outputs for an optimal lighting experience
- Easy and safe installation
- 0 - 10 volt dimming driver, dims to 10%
- The seamless, aluminum frame is durable and prevents light leak in the corners
- The satin white lens provides excellent shielding and fully luminous appearance for a contemporary design aesthetic
- CSA certified to meet US and Canadian standards for performance and safety
- Bulb Type: LED
- Voltage: 120 - 277 V
- CRI: 80
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Wattage	Lumens	Colour Temperature	Dimensions'	Price /Each
XI372	250EGS	20-39 W	2400, 3300, 4400	3500 K	1 x 4	
XI373	250EKS	20-39 W	2400, 3300, 4400	4000 K	1 x 4	
XI374	250ELS	20-39 W	2400, 3300, 4400	5000 K	1 x 4	
XI375	250E4S	20-39 W	2400, 3300, 4400	3500 K	2 x 2	
XI376	250E5S	20-39 W	2400, 3300, 4400	4000 K	2 x 2	
XI377	250E6S	20-39 W	2400, 3300, 4400	5000 K	2 x 2	
XI378	250CSL	32-52 W	4000, 5000, 6000	3500 K	2 x 4	
XI379	250CXS	32-52 W	4000, 5000, 6000	4000 K	2 x 4	
XI380	250E3S	32-52 W	4000, 5000, 6000	5000 K	2 x 4	

## TWR1 ALO WALL PACK LIGHT FIXTURE

- Durable choice for mounting above entryways and at loading docks
- Corrosion-resistant, die-cast aluminum construction
- To keep contaminants outside, the wall pack has a one-piece sealed gasket
- Replaces 70W to 250W metal halide lamps
- UL Listed to US and Canadian safety standards for wet locations, tested in accordance with IESNA LM-79 and LM-80 standards, DLC qualified
- Bulb Type: LED
- Overall Dim.: 14.25" W x 9.25" D x 7.25" H
- Colour: Dark Bronze
- Lumens: 3450
- CRI: 70
- Manufacturer's Warranty: 2 Year Limited



Model No.	Mfg. No.	Voltage	Wattage	Colour Temperature	Price /Each
XI416	254X97	120 - 277 V	29 W	4000 K	
XI418	254XC1	120 - 277 V	29 W	5000 K	
XI415	254X9X	347 V	87 W	4000 K	
XI417	254XC6	347 V	87 W	5000 K	

## OLWX1 WALL LUMINAIRE

- Combines a sleek, low-profile wall pack design with energy efficient, low maintenance LEDs for replacing up to 250W metal halide fixtures
- LEDs are protected behind a glass lens
- Easily mounts to recessed junction boxes with the included wall mount bracket, or for surface mounting and conduit entry with the included junction box with five 1/2" threaded conduit entry hubs
- Mounting accessories are available to convert the OLWX1 LED into an energy efficient flood light
- MVolt driver operates on any line voltage from 120-277V (50/60Hz)
- UL listed • Finish: Dark Bronze
- Overall Dim.: 7.5" W x 3" D x 8" H
- Housing Material: Cast Aluminum
- IP Rating: IP65
- Manufacturer's Warranty: 5 Years



Model No.	Mfg. No.	Wattage	Colour Temperature	Price /Each
XI486	225G1F	20 W	5000 K	

## BLC RECESSED LIGHT FIXTURE

- Delivers soft, glare-free, ambient lighting in a popular centre-basket design
- The slim profile of the luminaire, coupled with energy-saving LED technology make BLC the ideal choice for renovation or new construction
- Long-life LEDs, coupled with high-efficiency drivers, provide superior quantity and quality of illumination for extended service life
- 0 - 10 volt dimming driver, dims to 10%
- Fits standard into 15/16" and narrow 9/16" T-grid ceiling systems
- Long lasting LED technology maintains 80% of lumen output for 60000 hours
- Highly reflective and durable paint finish for improved aesthetics
- CSA, IC rated and DLC Standard
- Voltage: 120 - 277 V
- Lumens: 4000
- CRI: 80
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Colour Temperature	Dimensions'	Price /Each
XI360	2515TE	3500 K	2 x 2	
XI361	2515TF	4000 K	2 x 2	
XI362	2515TH	3500 K	2 x 4	
XI363	2515TJ	4000 K	2 x 4	

## FLOODLIGHT FIXTURE

- Cost-effective, energy-efficient, long-life solution for replacing metal halide or HPS floodlights
- UL Certified to meet US and Canadian standards, suitable for wet locations
- Die-cast aluminum main body with optimal thermal management that both enhances LED efficacy and extends component life
- Sealed against moisture or environmental contaminants
- Lamp Type: LED
- Housing Material: Aluminum
- Mount: Yoke
- Colour: Dark Bronze
- CRI: 70
- Colour Temperature: 4000 K
- Ingress Protection Rating: IP66
- Voltage: 120 - 277 V
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Description	Wattage	Lumens	Price /Each
XI412	2552M6	TFX1	57 W	7300	
XI413	2552ME	TFX2	94 W	13200	
XI414	2552MJ	TFX3	87 W	25600	

## D-SERIES MAST ARM MOUNT AREA LIGHT FIXTURE

- Features a sleek, modern design that blends seamlessly with the environment while creating outstanding photometric performance results
- Ideal applications include campuses, office complexes and retail sites
- Bulb Type: LED
- Voltage: 120 - 277 V
- Overall Dim.: 13" W x 27" D x 5" H
- CRI: 70
- Finish: Textured Dark Bronze
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Wattage	Lumens	Colour Temperature	Price /Each
XI381	225F1F	209 W	19771	4000 K	