

FOOD PLANT PENETRATING OIL

- General purpose lubricant for use on food processing equipment
- Penetrates and loosens rust, scale, corrosion, and dirt to free corroded parts and fasteners
- Does not contain silicones
- Approved for use in Canadian food processing facilities
- NSF Registered H1



Model No.	Mfg. No.	Size	Price /Each
AF203	73086	312 g	

FOOD PLANT CHAIN LUBE

- Keeps roller drive and conveyor chains lubricated
- Blend of synthetic lubricants and mineral oil
- Penetrates, lubricates and protects moving parts by reducing friction and wear
- Approved for use in Canadian food processing facilities
- NSF Registered H1



Model No.	Mfg. No.	Size	Price /Each
AF201	73056	340 g	

DI-ELECTRIC GREASE

- Non-curing silicone compound used for electrical sealing
- Waterproofs electrical connections and components
- Improves electrical performance
- NSF Registered H1



Model No.	Mfg. No.	Size	Price /Each
AF248	73082	284 g	

DETEX® FOOD GRADE EXTREME TEMP GREASE

- Premium, fully synthetic grease performs well in extreme temperature applications (-75°F - 510°F)
- NSF H1 grease can be used anywhere within a facility where incidental food contact may occur
- Non-melting formula is suitable for extended high temperature exposures
- Dye-free grease will not stain product or equipment
- Fortified with PTFE for enhanced lubrication and corrosion resistance
- Resists water washout through multiple wash cycles
- Metal and X-ray detectable plastic cap
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AH206	CS1014	369 g	
AH207	CS1055	55 Gal.	

CLEAR PENETRATING GREASE

- Features high tack, quick penetrating action, metal detectable plastic components, and clear lubricating gel
- High performance, versatile lubricant fortified with PTFE additives for enhanced lubrication
- Resists water washout
- Protects against corrosion
- Colour: Beige
- Odour: Acetone
- Appearance: Gas
- Boiling Point/Range: 132.8 °F (56 °C)
- Flash Point: 132.8 °F (56.0 °C)
- Tag Closed Cup
- Vapor Density: 2
- Viscosity: 260 cP @ 75°F (Concentrate)
- Heat of Combustion: > 30 kJ/g
- Temperature Range: 0°F (-18°C) to 400°F (204°C)



Model No.	Mfg. No.	Size	Price /Each
AH202	CO6716	11 oz.	

MULTI-PURPOSE FOOD PLANT GREASE

- Appearance: White Semi-Solid/Solid Grease
- Effective Temperature Range: -5°F - 370°F (-20.6°C to 187.8°C)
- Base Type: Aluminum Complex
- Flash Point: 221°C
- NSF Registered H1



Model No.	Mfg. No.	Size	Price /Each
AF202	73600	397 g	

DETEX® FOOD GRADE ELECTRONIC CLEANER

- Removes dirt, moisture, and oxides from electronic equipment
- NSF K6 electronic cleaner can be used anywhere within a facility where incidental food contact may occur
- Plastic-safe formula can be used on a variety of surfaces
- Fast drying and residue-free for efficient maintenance cycles
- VOC Compliant in all 50 states
- Metal and X-ray detectable packaging



Model No.	Mfg. No.	Size	Price /Each
AH215	CS8116	312 g	

LU210 FOOD GRADE SILICONE LUBRICANT

- 5% silicone formula
- Colourless, odourless low-viscosity lubricant
- Prevents sticking without transferring to end products
- Will not attack delicate surfaces such as styrene or urethane
- For slides, guide rails, knives, slicers, saws, grinders, dough mixers, guards, conveyors, food racks, ovens, bottling machines, heat sealing equipment, all food and drug processing equipment
- NSF registered category code H1



Model No.	Mfg. No.	Size	Price /Each
AA110	SC0210000	10 oz.	

SYNTHETIC FOOD GRADE OIL

- Includes PTFE for added lubricity
- Does not emulsify with water
- Waterproof
- Biodegradable
- Clear, non-staining
- Kosher approved
- For pumps, gear boxes, bearings, hydraulic systems, motors, chains, conveyors, general purpose lubrication
- NSF registered category code H1



Model No.	Mfg. No.	Size	Price /Each
AA525	TF23010	12 oz.	